

P62321 | TRUST premium plus Satin 250

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	252	± 6
Thickness DIN EN ISO 534	µm	252	± 6
	mil	9.9	± 0.2
Gloss BYK (60°) ISO 2813		19	± 5
Colour Elrepho UVO (D65) ISO 2469	L	95.3	± 0.5
	a	-0.1	± 0.3
	b	-1.2	± 0.5
	delta b	-0.1	± 0.5
il Pro2	L*M0	96.0	
	a*M0	-0.3	
	b*M0	-1.3	
	L*MI	96.2	
	a*MI	-0.3	
	b*MI	-2.0	
CIE whiteness (D65/10°) min. ISO 2469		> 92	
Opacity min. ISO 2469	%	> 95	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based systems

Compatibility

Compatible with all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

Declaration

FSC® Mix Credit (Available on request)

Certificates



BENEFITS AND PROPERTIES

- › Reproducibility by outstanding media colour consistency
- › Suitable for difficult spot colours
- › Extended homogeneous colour gamut
- › No matting due to a high absorption capacity
- › Optimisation of the absorption kinetics to the new printer generation

KEY APPLICATIONS

Proof & Prepress

- › Proofs for offset, gravure and screen
- › Printing
- › Contract, design and check proofs
- › Mock-ups

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 03/2021