

# E37064 | PRIMO Glossy 190

CAST-COATED GLOSSY PAPER

## PRODUCT SPECIFICATION \*

|  |                  |       |       |
|--|------------------|-------|-------|
| <b>Weight</b> DIN EN ISO 536                 | g/m <sup>2</sup> | 190   | ± 5   |
| <b>Thickness</b> DIN EN ISO 534              | µm               | 225   | ± 5   |
|  | mil              | 8.9   | ± 0.2 |
| <b>Gloss BYK (85°)</b> ISO 2813              |                  | 75    | ± 5   |
| <b>CIE whiteness (D65/10°) min.</b> ISO 2469 |                  | > 102 |       |

### Printability

Duplex printable

### Printing Technology

💧 Inkjet water-based

### Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

## BENEFITS & PROPERTIES

- Pin-sharp details
- High colour consistency and gamut
- Instant dry

## KEY APPLICATIONS

### Photo Retail

- Photo cards
- Photo prints
- Portraits
- Presentations
- Proposals
- Newsletters

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 09/2018