

# E82270 | SCM tec Matt 120

SPECIAL-COATED MATT PAPER

## PRODUCT SPECIFICATION \*

Weight	GB/T 451.2	g/m <sup>2</sup>	120	± 5
Thickness	GB/T 451.3	µm	150	± 7
		mil	5.9	± 0.3
Brightness	GB/T 7974		> 102	

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

💧 Inkjet water-based

### Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

## BENEFITS & PROPERTIES

- Extraordinary smooth surface
- Excellent line sharpness
- Vivid colours

## KEY APPLICATIONS

### Photo Retail

- Presentations
- Proposals
- Newsletters

### CAD- & GIS-Drawings

- CAD-drawings
- GIS applications (maps)

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 08/2019



**华邦古楼新材料有限公司**  
Winbon Schoeller New Materials Co., Ltd

[www.Felix-Schoeller.com](http://www.Felix-Schoeller.com)



**Felix Schoeller**  
DIGITAL MEDIA