

# F50100 | TRUST film Glossy 215

## MICROPOROUS COATED TRANSPARENT FILM

### PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	217	± 6
<b>Thickness</b> DIN EN ISO 534	µm	165	± 8
	mil	6.5	± 0.3
<b>Gloss BYK (60°)</b> ISO 2813		120	± 8
<b>Optical density</b>	Dmax UV	> 4	
<b>Screen ruling</b>	Bis zu	180 lpi	

#### Printability

Simplex printable

#### Printing Technology

💧 Inkjet water-based

#### Compatibility

Compatible with all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

### BENEFITS & PROPERTIES

- High density range
- Perfect dimensional stability
- High ink absorption
- Quick dry
- Excellent line and dot sharpness
- Good mechanical properties

### KEY APPLICATIONS

#### Proof & Prepress

- Positive and negative film separations for screen and pad printing

#### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 01/2016