

H62310 | TRUST commercial Satin 245

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION*

Weight DIN EN ISO 536	g/m ²	246	± 6
Thickness DIN EN ISO 534	µm	239	± 6
	mil	9.5	± 0.2
Gloss BYK (60°) ISO 2813		19	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94.2	± 0.5
	a	-0.2	± 0.3
	b	-2.6	± 0.5
	delta b	-0.2	± 0.5
il Pro2	L*M0	95.1	
	a*M0	-0.5	
	b*M0	-2.6	
	L*MI	95.3	
	a*MI	-0.3	
	b*MI	-2.9	
CIE whiteness (D65/10°) min. ISO 2469		> 94	
Opacity min. ISO 2469	%	> 94	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Compatible with all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

Declaration

FSC® Mix Credit (Available on request)

Certificates



BENEFITS & PROPERTIES

- › Reproducibility by outstanding media colour consistency
- › Large colour gamut
- › Pin-sharp details
- › Instant dry
- › Universal compatibility for printers and inks

KEY APPLICATIONS

Proof & Prepress

- › Proofs for offset, gravure and screen printing
- › Dot-proofs
- › Contract, design and check proofs
- › Mock-ups

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 08/2020