

H64210 | ULTRA Satin 200

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	198	± 6
Thickness DIN EN ISO 534	µm	205	± 6
	mil	8.1	± 0.2
Gloss BYK (60°) ISO 2813		19	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94,1	± 0,6
	a	-0,2	± 0,4
	b	-1,8	± 0,7
	delta b	9,8	± 0,7
CIE whiteness (D65/10°) min. ISO 2469		> 136	
Opacity min. ISO 2469	%	> 91	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

BENEFITS & PROPERTIES

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Water resistance
- Outstanding lay-flat performance

KEY APPLICATIONS

Photo Retail

- Photo cards
- Photo prints
- Portraits

Wall Decoration

- Posters
- Large-format photo prints

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 02/2016