

H64310 | ULTRA Satin 190

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	197	± 6
Thickness DIN EN ISO 534	µm	203	± 6
	mil	8.0	± 0.2
Gloss BYK (60°) ISO 2813		19	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94,7	± 0,8
	a	-0,2	± 0,5
	b	-2,6	± 0,8
	delta b	<0,7	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 94	
Opacity min. ISO 2469	%	> 92	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

BENEFITS & PROPERTIES

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Water resistance
- Outstanding lay-flat performance

KEY APPLICATIONS

Wall Decoration

- Posters
- Large-format photo prints

Sign & Display Graphics

- POS signage
- Exhibition graphics
- Photo prints
- Commercial posters for indoor and short-term outdoor applications

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 02/2016