

H64410 | TRUST commercial Glossy I90

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	197	± 6
Thickness DIN EN ISO 534	µm	200	± 6
	mil	7.9	± 0.2
Gloss BYK (60°) ISO 2813		50	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94,2	± 0,5
	a	-0,2	± 0,3
	b	-2,6	± 0,5
	delta b	<	0,7
il Pro2	L*M0	95,3	
	a*M0	-0,3	
	b*M0	-2,7	
	L*M1	95,3	
	a*M1	-0,3	
	b*M1	-3,0	
CIE whiteness (D65/10°) min. ISO 2469		> 94	
Opacity min. ISO 2469	%	> 93	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Compatible with all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

Certificates



Fogra 25488-2

BENEFITS & PROPERTIES

- Reproducibility by outstanding media colour consistency
- Large colour gamut
- Pin-sharp details
- Instant dry
- Universal compatibility for printers and inks

KEY APPLICATIONS

Proof & Prepress

- Proofs for offset, gravure and screen printing
- Dot-proofs
- Contract, design and check proofs
- Mock-ups

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 01/2016