

H655 I I | TRUST premium Flat Matt 200

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	201	± 6
Thickness DIN EN ISO 534	µm	207	± 6
	mil	8.1	± 0.2
Gloss BYK (60°) ISO 2813		19	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94,2	± 0,5
	a	-0,2	± 0,3
	b	-2,6	± 0,5
	delta b	<	0,7
il Pro2	L*M0	95,3	
	a*M0	-0,3	
	b*M0	-2,7	
	L*M1	95,3	
	a*M1	-0,3	
	b*M1	-3,0	
CIE whiteness (D65/10°) min. ISO 2469		> 93	
Opacity min. ISO 2469	%	> 94	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Compatible with all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

Certificates



Fogra 28383-5

BENEFITS & PROPERTIES

- Reproducibility by outstanding media colour consistency
- Suitable for spot colours
- Large colour gamut
- No matting due to a high ink load
- Instant dry

KEY APPLICATIONS

Proof & Prepress

- Proofs for offset, gravure and screen printing
- Dot-proofs
- Contract, design and check proofs
- Mock-ups

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 01/2016