

# H90130 | SLP rc Extra Glossy 225

RESIN-COATED PAPER WITH SLP

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	226	± 7
<b>Thickness</b> DIN EN ISO 534	µm	214	± 7
	mil	8.4	± 0.3
<b>Gloss BYK (60°)</b> ISO 2813		92	± 5
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	93,5	± 0,6
	a	-0,3	± 0,4
	b	-1,6	± 0,6
	delta b	11,9	± 0,6
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 144	
<b>Opacity min.</b> ISO 2469	%	> 92	

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

🔴 Inkjet solvent

🔵 Inkjet latex

🟣 Inkjet UV

## BENEFITS & PROPERTIES

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- Optimum handling properties
- High light fastness
- Outdoor durability
- Outstanding lay-flat performance
- Fast dry
- PVC free

## KEY APPLICATIONS

### Wall Decoration

- Posters
- Large-format photo prints

### Sign & Display Graphics

- POS signage
- Exhibition graphics
- Photo prints
- Commercial posters for indoor and outdoor applications
- POS signage

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 02/2016