

# H91130 | SLP RC EXTRA GLOSSY | 275

RESIN-COATED PAPER WITH SLP

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	278	± 7
<b>Thickness</b> DIN EN ISO 534	µm	258	± 7
	mil	10.2	± 0.27
<b>Gloss BYK (60°)</b> ISO 2813		22	± 5
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	93.4	± 0.6
	a	-0.3	± 0.4
	b	-1.6	± 0.6
	delta b	11.6	± 0.6
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 144	
<b>Opacity min.</b> ISO 2469	%	> 94	

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

🔥 Inkjet solvent

💧 Inkjet latex

💜 Inkjet UV

### Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers.

### Certificates

Certified for  
HP Latex Inks

Certified for HP Latex Inks

## BENEFITS AND PROPERTIES

- › Pin-sharp details
- › Vivid colours
- › High colour consistency and gamut
- › Optimum handling properties
- › High light fastness
- › Outdoor durability
- › Outstanding lay-flat performance
- › Fast dry
- › PVC free
- › Certified for HP Latex Inks (more information: <https://www.printos.com/ml/#/medialocator>)

## KEY APPLICATIONS

### Sign & Display Graphics

- › POS signage
- › Exhibition graphics
- › Photo prints
- › Commercial posters for indoor and outdoor applications

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 03/2021

