

H91230 | SLP rc Satin 275

RESIN-COATED PAPER WITH SLP

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	276	± 7
Thickness DIN EN ISO 534	µm	256	± 7
	mil	10.1	± 0.3
Gloss BYK (60°) ISO 2813		22	± 5
Colour Elrepho UVO (D65) ISO 2469	L	93,5	± 0,6
	a	-0,3	± 0,4
	b	-1,6	± 0,6
	delta b	11,4	± 0,6
CIE whiteness (D65/10°) min. ISO 2469		> 143	
Opacity min. ISO 2469	%	> 96	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

🟠 Inkjet solvent

🟡 Inkjet latex

🟣 Inkjet UV

Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers

BENEFITS & PROPERTIES

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- Optimum handling properties
- High light fastness
- Outdoor durability
- Outstanding lay-flat performance
- Fast dry
- PVC free

KEY APPLICATIONS

Sign & Display Graphics

- POS signage
- Exhibition graphics
- Photo prints
- Commercial posters for indoor and outdoor applications

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 02/2016