


J24470 TRUE rag watercolour Matt 310

Special-Coated Rag Paper

Printability

- simplex printable



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	310	± 20
Thickness	DIN EN ISO 534	µm	520	± 20
	DIN EN ISO 536	mil	20.5	± 0.79
Colour Elrepho UVO (D65)	ISO 2469	L	97,3	± 1,0
		a	0,4	± 0,5
		b	2,2	± 0,8
		delta b	-0,5	± 0,6
CIE Whiteness (D65/10°) min.	ISO 2469		> 79	
Opacity min.	ISO 2469	%	> 98	

Printing Technology

- 💧 Inkjet water-based

Key Applications

- Professional Photo & Fine Art
- Portfolio folders
- Exhibitions
- Art reproduction

Benefits & Properties

- Watercolour textured surface
- Pin-sharp details
- High colour consistency and gamut
- 100 % cotton
- Free of optical brighteners
- Water resistance

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER