

J24670 | TRUE rag smooth Matt 310

SPECIAL-COATED RAG PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	310	± 20
Thickness DIN EN ISO 534	µm	440	± 40
	mil	17.3	± 1.6
Colour Elrepho UVO (D65) ISO 2469	L	97.3	± 1.0
	a	0.4	± 0.5
	b	2.2	± 0.8
	delta b	-0.5	± 0.6
CIE whiteness (D65/10°) min. ISO 2469		> 79	
Opacity min. ISO 2469	%	> 98	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, etc.

BENEFITS & PROPERTIES

- Smooth surface
- Pin-sharp details
- High colour consistency and gamut
- 100 % cotton
- Free of optical brighteners
- Water resistance

KEY APPLICATIONS

Professional Photo & Fine Art

- Professional photography
- High-end photo prints
- Portfolio folders
- Exhibitions
- Art reproduction

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 11/2019