

J43270 | INSPIRE canvas Matt 340

SPECIAL-COATED FABRIC

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	340	± 25
Thickness DIN EN ISO 534	µm	400	± 25
	mil	15.7	± 1.0
Colour Elrepho UVO (D65) ISO 2469	L	94,7	± 1,0
	a	0	± 0,5
	b	1,1	± 1,0
	delta b	3,5	± 1,0
CIE whiteness (D65/10°) min. ISO 2469		> 90	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc. Profiled for HP Latex printers.

BENEFITS & PROPERTIES

- Large colour gamut
- Instant dry
- Perfect stretching and framing performance
- High light fastness with pigmented inks
- Profiled for HP Latex Inks (more information: <https://www.printos.com/ml/#/medialocator>)

KEY APPLICATIONS

Wall Decoration

- Canvas on stretcher frames
- Photos
- Art reproduction

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 06/2017