

J43270 INSPIRE canvas Matt 340

Special-Coated Fabric

Printability

- simplex printable

Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	340	± 25
Thickness	DIN EN ISO 534	µm	400	± 25
	DIN EN ISO 536	mil	15.7	± 0.98
Gloss BYK	ISO 2813	20°	0.0	± 0.0
Gloss BYK	ISO 2813	60°	70	± 0
Gloss BYK	ISO 2813	85°	0.0	± 0.0
Colour Elrepho UVO (D65)	ISO 2469	L	94,7	± 0,5
		b	1,1	± 1
		delta b	3,5	± 1

Printing Technology

- Inkjet water-based
- Inkjet Latex

Certificates

- Ökotex

Key Applications

- Art reproduction
- Canvas on frame
- Photos
- Wall Decoration

Benefits & Properties

- Instant dry
- Large colour gamut
- High light fastness
- Perfect stretching and framing performance
- High light fastness with pigmented inks
- Free of harmful substances (certified by Oeko-Tex® Standard 100)
- Profiled for HP Latex Inks (more information: <https://www.printos.com/ml/#/medialocator>)

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

[felix-schoeller.com](https://www.felix-schoeller.com)



FELIX SCHOELLER