

J43680 INSPIRE canvas Matt 340

Special-Coated Fabric

Printability

- simplex printable

Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	340	± 25
Thickness	DIN EN ISO 534	µm	400	± 25
	DIN EN ISO 536	mil	15.7	± 0.98
Gloss BYK	ISO 2813	20°	0.0	± 0.0
Gloss BYK	ISO 2813	60°	80	± 0
Gloss BYK	ISO 2813	85°	0.0	± 0.0
Colour Elrepho UVO (D65)	ISO 2469	L	94,3	± 0,5
		a	-0,8	± 0,5
		b	2,4	± 1
		delta b	2,9	± 1

Printing Technology

- 💧 Inkjet water-based

Certificates

- Ökotex

Key Applications

- Art reproduction
- Canvas on frame
- Photos
- Wall Decoration

Benefits & Properties

- Instant dry
- Large colour gamut
- High light fastness
- Perfect stretching and framing performance
- High light fastness with pigmented inks
- Free of harmful substances (certified by Oeko-Tex® Standard 100)

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER