

# J53230 | SLP Satin 200

COATED PAPER WITH SLP

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	204	± 7
<b>Thickness</b> DIN EN ISO 534	µm	192	± 7
	mil	7.6	± 0.27
<b>Gloss BYK (60°)</b> ISO 2813		18	± 5
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	96.8	± 0.5
	a	0.2	± 0.3
	b	2.6	± 0.6
	delta b	12.6	± 0.8
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 136	
<b>Opacity min.</b> ISO 2469	%	> 91	

## BENEFITS & PROPERTIES

- Excellent image quality with brilliant colours
- Optimum handling properties
- Outdoor durability
- High wet strength
- Fast dry
- PVC free
- Certified for HP Latex Inks (more information: <https://www.printos.com/ml/#/medialocator>)

## KEY APPLICATIONS

### Sign & Display Graphics

- POS signage
- Exhibition graphics
- Commercial posters for indoor and outdoor applications

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

🟠 Inkjet solvent

🟡 Inkjet latex

🟣 Inkjet UV

### Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers. Certified for HP Latex printers.

### Certificates

Certified for  
**HP Latex Inks**

Certified for HP Latex Inks

Version 04/2017