

J53330 | SLP Matt 200

COATED PAPER WITH SLP

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	206	± 7
Thickness DIN EN ISO 534	µm	194	± 7
	mil	7.6	± 0.3
Colour Elrepho UVO (D65) ISO 2469	L	97.7	± 0.5
	a	0.2	± 0.3
	b	2.4	± 0.6
	delta b	12.4	± 0.8
CIE whiteness (D65/10°) min. ISO 2469		> 136	
Opacity min. ISO 2469	%	> 91	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

🟠 Inkjet solvent

🟡 Inkjet latex

🟣 Inkjet UV

Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers. HP Latex certification available on request.

Declaration

FSC® Mix Credit (Available on request)

BENEFITS & PROPERTIES

- Excellent image quality with brilliant colours
- High scratch resistance
- Low gloss level, minimised differential gloss
- Optimum handling properties
- Outdoor durability
- Fast dry
- PVC free
- No waviness at any latex printer
- HP Latex certification available on request

KEY APPLICATIONS

Sign & Display Graphics

- POS signage
- Exhibition graphics
- Commercial posters for indoor and outdoor applications

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 09/2018