

J80110 | PRECISE Semi Gloss 100

MICROPOROUS COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	100	± 5
Thickness DIN EN ISO 534	µm	98	± 7
	mil	3.8	± 0.3
Gloss BYK (60°) ISO 2813		30	± 5
Colour Elrepho UVO (D65) ISO 2469	L	95,2	± 1,0
	a	0,1	± 0,5
	b	0,5	± 1,0
	delta b	10,5	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 133	
Opacity min. ISO 2469	%	> 86	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, and Memjet etc. Profiled for HP PageWide XL.

Declaration

FSC® Mix Credit (Available on request)

BENEFITS & PROPERTIES

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- Instant dry
- Profiled for HP PageWide XL

KEY APPLICATIONS

Wall Decoration

- Posters
- Large-format photo prints

Sign & Display Graphics

- POS signage
- Exhibition graphics
- Photo prints
- Commercial posters for indoor and short-term outdoor applications

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 03/2017