

J80111 TRUST economy Semi Gloss 100

Microporous Coated Paper

Printability

- simplex printable

MICROPOROUS COLOR RECEIVER LAYER

RAW BASE PAPER



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	100	± 5
Thickness	DIN EN ISO 534	µm	98	± 7
	DIN EN ISO 536	mil	3.9	± 0.3
Gloss BYK	ISO 2813	60°	29	± 5
i1 Pro2		L*M0	96,5	
		a*M0	1,7	
		b*M0	-5,4	
		L*MI	96,5	
		a*MI	2,1	
		b*MI	-8,2	
Colour Elrepho UVO (D65)	ISO 2469	L	94,7	± 1
		a	0,1	± 0,5
		b	-0,1	± 1
		delta b	9,5	± 0,8
CIE Whiteness (D65/10°) min.	ISO 2469		> 129	
Opacity min.	ISO 2469	%	> 86	

Printing Technology

- 💧 Inkjet water-based systems

Key Applications

- Check Proofs
- Halftone proof

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER

J80111 TRUST economy Semi Gloss 100

Microporous Coated Paper

Benefits & Properties

- Instant dry
- Pin-sharp details
- Large colour gamut
- Reproducibility by outstanding media colour consistency

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

[felix-schoeller.com](https://www.felix-schoeller.com)



FELIX SCHOELLER