

# J80270 | SCM pro Matt 90

SPECIAL-COATED MATT PAPER

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	96	± 7
<b>Thickness</b> DIN EN ISO 534	µm	127	± 8
	mil	5.0	± 0.3
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	95,8	± 1,0
	a	-0,2	± 0,5
	b	-1,2	± 1,0
	delta b	12,3	± 0,8
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 145	
<b>Opacity min.</b> ISO 2469	%	> 87	

## BENEFITS & PROPERTIES

- Very smooth surface
- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- Meets criteria for permanence according ISO 9706
- Profiled for HP PageWide XL

## KEY APPLICATIONS

### Photo Retail

- Presentations
- Proposals
- Newsletters

### CAD- & GIS-Drawings

- CAD-drawings
- GIS applications (maps)

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

💧 Inkjet water-based

### Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc. Profiled for HP PageWide XL machines.

### Certificates



DIN EN ISO 9706

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 12/2018