


J80273 SCM pro terra Matt 95

DRAFT | Special-Coated Matt Paper

Printability

- simplex printable



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	94	
Thickness	DIN EN ISO 534	µm	142	
		mil	5,6	
Colour Elrepho UVO (D65)	ISO 2469	L	83,9	
		a	2,5	
		b	6,9	
		delta b	4,2	
CIE Whiteness (D65/10°) min.	ISO 2469		> 50	
Opacity min.	ISO 2469	%	> 98	

Printing Technology

- Inkjet water-based

Key Applications

- POS signs
- Exhibition graphics
- Sign & Display Graphics

Benefits & Properties

- Pin-sharp details
- High colour consistency and gamut
- Vivid colours
- Excellent line sharpness
- Naturally recycled surface
- Base paper made of 65 % recycled fibers
- Made in Germany

Version: 01.2024

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER