

J82111 | TRUST economy Semi Gloss 125

MICROPOROUS COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	125	± 5
Thickness DIN EN ISO 534	µm	125	± 7
	mil	4.9	± 0.3
Gloss BYK (60°) ISO 2813		30	± 5
Colour Elrepho UVO (D65) ISO 2469	L	96	± 1,0
	a	0.0	± 0,5
	b	0,8	± 1,0
	delta b	9,8	± 0,8
il Pro2	L*M0	97,5	
	a*M0	1,6	
	b*M0	-5,1	
	L*M1	97,5	
	a*M1	2,0	
	b*M1	-7,7	
CIE whiteness (D65/10°) min. ISO 2469		> 130	
Opacity min. ISO 2469	%	> 88	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Compatible with all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

BENEFITS & PROPERTIES

- Reproducibility by outstanding media colour consistency
- Large colour gamut
- Pin-sharp details
- Instant dry

KEY APPLICATIONS

Proof & Prepress

- Proofs for offset, gravure and screen printing
- Dot-proofs
- Check proofs

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 01/2016