


J93274 SCM pro Matt 230

Special-Coated Matt Paper

Printability

- duplex printable



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	235	± 7
Thickness	DIN EN ISO 534	µm	276	± 10
	DIN EN ISO 536	mil	10.9	± 0.39
Colour Elrepho UVO (D65)	ISO 2469	L	95,8	± 1
		a	-0,2	± 0,5
		b	-1,2	± 1
		delta b	12,3	± 0,8
CIE Whiteness (D65/10°) min.	ISO 2469		> 145	
Opacity min.	ISO 2469	%	> 96	

Printing Technology

- Inkjet water-based

Key Applications

- Newsletter
- Photo Retail
- Presentations
- Menu cards
- Photos
- Photo books

Benefits & Properties

- Pin-sharp details
- High colour consistency and gamut
- Vivid colours
- High colour consistency
- High whiteness
- Meets criteria for permanence according ISO 9706

Version: 11/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER