

M52110 | LIVE photo Glossy 250

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	251	± 6
Thickness DIN EN ISO 534	µm	251	± 6
	mil	9.9	± 0.23
Gloss BYK (60°) ISO 2813		62	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94.1	± 0.7
	a	-0.2	± 0.5
	b	-1.8	± 0.7
	delta b	9.8	± 0.8
CIE whiteness (D65/10°) min. ISO 2469		> 136	
Opacity min. ISO 2469	%	> 92	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial Inkjet Minilab Printsystems like Noritsu, Fuji and Epson

Declaration

FSC® Mix Credit (Available on request)

BENEFITS & PROPERTIES

- Maximum scratch resistance
- Higher gloss level and excellent haptic performance
- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Water resistance
- Outstanding lay-flat performance

KEY APPLICATIONS

Dry Minilab Inkjet

- Photo and panorama prints
- Portraits
- Greeting cards
- Photo gifts

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 11/2021