

# M52710 | LIVE photo Lustre 250

MICROPOROUS RESIN-COATED PAPER

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	246	± 6
<b>Thickness</b> DIN EN ISO 534	µm	241	± 6
	mil	9.5	± 0.23
<b>Gloss BYK (60°)</b> ISO 2813		24	± 5
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	94.2	± 0.7
	a	-0.2	± 0.5
	b	-1.8	± 0.7
	delta b	9.8	± 0.8
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 136	
<b>Opacity min.</b> ISO 2469	%	> 92	

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

💧 Inkjet water-based

### Compatibility

Compatible for all inkjet minilab print systems such as Noritsu, Fuji and Epson with the exception of Epson D3000.

### Declaration

FSC® Mix Credit (Available on request)

## BENEFITS & PROPERTIES

- Maximum scratch resistance
- Excellent haptic performance
- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Water resistance
- Outstanding lay-flat performance

## KEY APPLICATIONS

### Dry Minilab Inkjet

- Photo and panorama prints
- Portraits
- Greeting cards
- Photo gifts

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 08/2018