

M62610 | LIVE photo Pyramid 250

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	249	± 6
Thickness DIN EN ISO 534	µm	256	± 6
	mil	10.1	± 0.3
Gloss BYK (60°) ISO 2813		11	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94,0	± 0,7
	a	-0,2	± 0,5
	b	-1,8	± 0,7
	delta b	9,8	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 136	
Opacity min. ISO 2469	%	> 92	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial Inkjet
Minilab Printsystems like Noritsu, Fuji and
Epson

BENEFITS & PROPERTIES

- Maximum scratch resistance
- Excellent haptic performance
- Extraordinary hexagonal texture
- Unique look and feel
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Water resistance
- Outstanding lay-flat performance
- Copy-protected

KEY APPLICATIONS

Photo Retail

- Photo and panorama prints
- Portraits
- Greeting cards
- Photo gifts

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 05/2016