
M62610 LIVE photo Pyramid 250

Microporous Resin-Coated Paper

Printability

· simplex printable



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m²	248	± 6
Thickness	DIN EN ISO 534	μm	255	± 6
	DIN EN ISO 536	mil	10.0	± 0.23
Gloss BYK	ISO 2813	60°	15	± 5
Colour Elrepho UVO (D65)	ISO 2469	L	94	± 0,7
		а	-0,2	± 0,5
		b	-1,8	± 0,7
		delta b	9,8	± 0,8
CIE Whiteness (D65/10°) min.	ISO 2469		> 136	
Opacity min.	ISO 2469	%	> 92	

Printing Technology



Key Applications

- · Greeting and invitation cards
- · Photo and panorama prints
- Photo gifts
- · Photo Retail



Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

M62610 LIVE photo Pyramid 250

Microporous Resin-Coated Paper

Benefits & Properties

- · Pin-sharp details
- · High colour consistency and gamut
- · Vivid colours
- · High colour consistency
- · Maximum scratch resistance
- · Excellent haptic performance
- · Unique look and feel
- · Extraordinary hexagonal texture
- · Water resistance
- · High opacity
- · High light fastness
- · Outstanding lay-flat performance
- · Copy-protected

Version: 10/2023

