

M64710 | LIVE photo Lustre 300

MICROPOROUS RESIN-COATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	303	± 7
Thickness DIN EN ISO 534	µm	295	± 6
	mil	11.6	± 0.2
Gloss BYK (60°) ISO 2813		25	± 5
Colour Elrepho UVO (D65) ISO 2469	L	94,4	± 0,7
	a	-0,2	± 0,5
	b	-1,8	± 0,7
	delta b	9,8	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 136	
Opacity min. ISO 2469	%	> 92	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

💧 Inkjet water-based

Compatibility

Compatible for all inkjet minilab print systems such as Noritsu, Fuji and Epson with the exception of Epson D3000.

BENEFITS & PROPERTIES

- Maximum scratch resistance
- Excellent haptic performance
- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Water resistance
- Outstanding lay-flat performance

KEY APPLICATIONS

Dry Minilab Inkjet

- Photo and panorama prints
- Portraits
- Greeting cards
- Photo gifts

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 08/2018