

WV50428 | INSPIRE wallpaper Matt 130

SPECIAL-COATED NONWOVEN

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	130	± 10
Thickness DIN EN ISO 534	µm	240	± 25
	mil	9,4	± 0,6
Colour Elrepho UVO (D65) ISO 2469	L	97,1	± 1,0
	a	-0,1	± 0,3
	b	2,4	± 0,8
	delta b	2,9	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 90	
Opacity min. ISO 2469	%	> 85	

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

● Dry toner systems

Certificates



Xeikon

BENEFITS & PROPERTIES

- Photorealistic print results
- High dimensional stability
- Perfect handling and edge-to-edge alignment
- Paste-the-wall wallpaper
- Instant dry
- Perfect dry stripability
- PVC free and free of plasticizers
- Flame retardancy B-s1,d0 (according DIN EN 13501-1)
- Qualified for Xeikon printing systems (more information: <https://printmedia.xeikon.com>)
- FSC® mix credit (available on request)

KEY APPLICATIONS

Wall Decoration

- Personalized wallpapers
- Photo wallpapers

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 06/2016