

# WV52430 | INSPIRE wallpaper Satin I30

COATED NONWOVEN

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	134	± 10
<b>Thickness</b> DIN EN ISO 534	µm	175	± 25
	mil	6.9	± 0.6
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	95,5	± 1,0
	a	-0,1	± 0,3
	b	2,7	± 0,8
	delta b	<0,5	
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 72	
<b>Opacity min.</b> ISO 2469	%	> 87	

## BENEFITS & PROPERTIES

- Photorealistic print results
- High dimensional stability
- Perfect handling and edge-to-edge alingment
- Paste-the-wall wallpaper
- Instant dry
- Perfect dry stripability
- PVC free and free of plasticizers
- Flame retardancy B-s1-d0 (according DIN EN 13501-1)
- Qualified for Xeikon machines (more information: <https://printmedia.xeikon.com>)
- Certified for HP Latex Inks (more information: <https://www.printos.com/ml/#/medialocator>)
- FSC® mix credit (available on request)

## KEY APPLICATIONS

### Wall Decoration

- Personalized wallpapers
- Photo wallpapers

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

### Printability

Simplex printable

### Printing Technology

- ◆ Inkjet latex
- Dry toner systems

### Compatibility

Certified for HP Latex printers. Qualified for Xeikon machines.

### Certificates



Xeikon

Certified for  
HP Latex Inks

Certified for HP Latex Inks

Version 06/2017