
W70606 E-PHOTO® Lustre 190

Resin-Coated Paper with Primer

Printability

· duplex printable



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m²	187	± 6
Thickness	DIN EN ISO 534	μm	184	± 6
	DIN EN ISO 536	mil	7.3	± 0.23
Gloss BYK	ISO 2813	60°	30	± 5
CIE Whiteness (D65/10°) min.	ISO 2469		> 140	
Opacity min.	ISO 2469	%	> 91	

Printing Technology

- Indigo systems
- Dry Toner Systems

Key Applications

- · Business cards
- · Business reports
- · Cookbooks
- Cover
- · Greeting and invitation cards
- · High quality brochures
- · Menu cards
- · Photos
- · Photo books
- · Photo Merchandise
- · Photo cards

Certificates

- · WIR 200-years-permanence
- · HP Indigo Certified Media
- · HP Indigo Best Performing Substrate
- · Xeikon
- · FSC on request

Version: 08/2023



This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.



W70606 E-PHOTO® Lustre 190

Resin-Coated Paper with Primer

Benefits & Properties

- · Excellent runnability
- · Excellent toner adhesion
- · Guaranteed look and feel of traditional photographic paper
- High whiteness
- · No whitebreak (even without scoring)
- · FSC® mix credit
- · High ageing resistance (200+ years tested by Wilhelm Institute of Research)

Version: 08/2023



