

W71606 | E-PHOTO® Lustre 290

RESIN-COATED PAPER WITH PRIMER

E-PHOTO®

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	284	± 6
Thickness DIN EN ISO 534	µm	289	± 6
	mil	11.4	± 0.23
Gloss BYK (60°) ISO 2813		30	± 5
CIE whiteness (D65/10°) min. ISO 2469		> 90	
Opacity min. ISO 2469	%	> 95	

BENEFITS & PROPERTIES

- Guaranteed look and feel of traditional photographic paper
- Excellent runnability
- Excellent toner adhesion
- Water and dirt resistance
- High whiteness
- No whitebreak, even without scoring
- High ageing resistance (200+ years tested by Wilhelm Institute of Research)
- Certified by HP Indigo
- Certified for Konica Minolta AccurioPress C83hc
- Certified for Ricoh Pro C72210x and Rico Pro C9210
- FSC® mix credit (available on request)

KEY APPLICATIONS

Photo Merchandise

- Photo books
- Photo prints
- Greeting cards
- Cooking books
- Menu cards
- Business cards and further more

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Printability

Duplex printable

Printing Technology

- Indigo systems

Compatibility

Certified for HP Indigo

Declaration

FSC® Mix Credit (Available on request)

Certificates

HP Indigo
Certified Media

HP Indigo Certified Media

BEST PERFORMING
SUBSTRATE

HP Indigo Best Performing Substrate



WIR 200-years-permanence

Version 03/2017

 **Felix Schoeller**
DIGITAL MEDIA