

W71606 E-PHOTO® Lustre 290

Resin-Coated Paper with Primer

Printability

- duplex printable



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	282	± 6
Thickness	DIN EN ISO 534	µm	287	± 6
	DIN EN ISO 536	mil	11,4	± 0.23
CIE Whiteness (D65/10°) min.	ISO 2469		> 90	
Opacity min.	ISO 2469	%	> 94	

Printing Technology

- Indigo systems
- Dry toner systems

Certificates

- HP Indigo Certified Media
- HP Indigo Best Performing Substrate
- WIR 200-years-permanence
- FSC on request

Key Applications

- Business cards
- Cookbooks
- Greeting and invitation cards
- Menu cards
- Photos
- Photo books
- Photo Merchandise
- Photo cards
- and more

Benefits & Properties

- Excellent runnability
- Excellent toner adhesion
- Guaranteed look and feel of traditional photographic paper
- High whiteness
- No whitebreak (even without scoring)
- FSC® mix credit
- High ageing resistance (200+ years tested by Wilhelm Institute of Research)

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER