

W7645 I | STYLine® New York Matt 150

COATED NONWOVEN

STYLine®

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	152	± 6
Thickness DIN EN ISO 534	µm	247	± 10
	mil	9.7	± 0.4
Colour Elrepho UVO (D65) ISO 2469	L	97,7	± 0,8
	a	0,1	± 0,5
	b	2,7	± 0,8
	delta b	3,4	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 97	
Opacity min. ISO 2469	%	> 89	

BENEFITS & PROPERTIES

- Individually developed for digital printing technologies
- Soft-touch feeling
- PVC free coating
- Homogeneous formation
- Excellent printability
- Perfect handling and edge-to-edge alignment
- Excellent dry strippability
- Excellent smudge and water-resistance
- Low gloss level, minimized differential gloss
- Flame retardancy C-s1-d0 (according DIN EN 13501-1)
- Free of harmful substances (STANDARD 100 by OEKO-TEX®, Zert.Nr. 17.0.16395)
- Certified for HP Latex Inks (more information: <https://www.printos.com/ml/#/medialocator>)

KEY APPLICATIONS

Digital Wallpaper

- Personalised wallpapers
- Photo wallpapers

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Printability

Simplex printable

Printing Technology

🔥 Inkjet solvent

💧 Inkjet latex

Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers. Certified for HP Latex Inks.

Certificates



**FLAME
RETARDANCY**

Flame retardancy



Oeko-Tex

**Certified for
HP Latex Inks**

Certified for HP Latex Inks

Version 06/2017