

# W76471 | STYLine® New York Matt 170

COATED NONWOVEN

# STYLine®

## PRODUCT SPECIFICATION \*

<b>Weight</b> DIN EN ISO 536	g/m <sup>2</sup>	172	± 6
<b>Thickness</b> DIN EN ISO 534	µm	271	± 8
	mil	10,7	± 0,3
<b>Colour Elrepho UVO (D65)</b> ISO 2469	L	97,7	± 0,8
	a	0,1	± 0,5
	b	2,7	± 0,8
	delta b	3,4	± 0,8
<b>CIE whiteness (D65/10°) min.</b> ISO 2469		> 97	
<b>Opacity min.</b> ISO 2469	%	> 90	

## BENEFITS & PROPERTIES

- Individually developed for digital printing technologies
- Soft-touch feeling
- PVC free coating
- Homogeneous formation
- Excellent printability
- Perfect handling and edge-to-edge alignment
- Excellent dry strippability
- Excellent smudge and water-resistance
- Low gloss level, minimized differential gloss
- Flame retardancy C-s1-d0 (according DIN EN 13501-1)
- Free of harmful substances (STANDARD 100 by OEKO-TEX®, Zert.Nr. 17.0.16395)
- Certified for HP Latex Inks (more information: <https://www.printos.com/ml/#/medialocator>)

## KEY APPLICATIONS

### Digital Wallpaper

- Personalised wallpapers
- Photo wallpapers

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

### Printability

Simplex printable

### Printing Technology

🔴 Inkjet solvent

🔵 Inkjet latex

### Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers. Certified for HP Latex Inks.

### Certificates



**FLAME  
RETARDANCY**

Flame retardancy



Oeko-Tex

**Certified for  
HP Latex Inks**

Certified for HP Latex Inks

Version 06/2017