

ZI 1490 | JET-LINE base Matt 90

UNCOATED SURFACE-TREATED PAPER

JET-LINE

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	90	± 6
Thickness DIN EN ISO 534	µm	120	± 6
	mil	4.7	± 0.2
CIE whiteness (D65/10°) min. ISO 2469		> 166	
Opacity min. ISO 2469	%	> 94	

BENEFITS & PROPERTIES

- Excellent line sharpness
- Rich colours
- High colour consistency
- Deep blacks
- High opacity
- Inline finishing possible
- Cost-effective
- Meets ColorPRO Technology standards
- Profiled for HP PageWide XL

KEY APPLICATIONS

CAD- & GIS-Drawings

- CAD drawings
- GIS applications (maps)
- Transpromo
- Transactionals

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Printability

Duplex printable

Printing Technology

- Inkjet water-based
- High-speed inkjet systems

Compatibility

Can be used on all common commercial high-speed inkjet as well as thermal and piezo water-based printing systems. Profiled for HP PageWide XL machines.

Declaration

FSC® Mix Credit (Available on request)

Certificates



ColorPRO Technology

Version 03/2017